

Real-Time Measurement of Total Carbon



Total Carbon Analyzer Model TCA08

KEY FEATURES

- Continuous analysis of Total Carbon content of aerosol
- Combine with Aethalometer® to derive OC/EC
- Sampling time 20 min to 24 hours
- Uses ambient air as carrier gas
- Rugged, All-Steel Construction
- Easy installation, operation and maintenance

European Patent EP19213028 and other patents pending



Developed and manufactured in
Europe by Aerosol d.o.o., Slovenia

APPLICATIONS

- Air Quality monitoring
- Health Effects, Climate Change research
- Emissions testing

Product specifications

MEASUREMENT PRINCIPLE

Two identical flow channels for sampling and analysis. Sample is collected on 47-mm quartz fiber filter in stainless-steel combustion chamber*. At end of sampling timebase, collection flow is switched to second channel while first channel is analyzed. Collected sample is flash-heated to convert all Carbon to CO₂. Ambient air is used as “analytical” carrier gas at low flow rate. The baseline level of CO₂ in ambient air is determined before and after the heating cycle. Large pulse of CO₂ in analytical flow is integrated over ambient baseline to determine Total Carbon content of sample.

*European Patent EP19213028 and other patents pending

“NO GLASS, NO GAS”

No glass. Chambers constructed entirely from stainless steel. Rugged FeCrAl alloy heating elements.

No gas. Uses ambient air as carrier: does not need any specialty gas supplies.

No catalyst.

DETERMINATION OF OC AND EC

BC data from Aethalometer AE33 is used to derive EC. OC is obtained by simple subtraction: $OC = TC - EC$. The relationship between BC and EC depends on aerosol composition and the thermal protocol used for ‘EC’ assignment.

COMBINATION WITH AE33 AETHALOMETER

Cable connection: TCA software receives Aethalometer data.

SAMPLING

Standard flow rate of 16.7 SLPM (1 m³/h), provided by closed-loop stabilized internal pump. Standard PM2.5 inlet is included. Sampled air stream must be non-condensing (RH < 90% at instrument temperature).

Opening altitude 0 ~ 3000 m.

Ambient meteorological sensor (P, T, RH) is included to control sampling flow to ambient volumetric conditions.

TIME RESOLUTION

Timebase for sampling and analysis is adjustable from 20 minutes to 24 hours. Default setting is 1 hour.

ANALYTICAL PERFORMANCE

Limit of Detection: 300 ng C/m³ (1-h timebase, 16.7 LPM flow)

Range: 300 ng/m³ to 300.000 ng/m³ of Total Carbon

OPERATOR INTERFACE

21-cm color touch-screen with status indicator LED's.

REMOTE MANAGEMENT

Network ready for remote management and data transfer.

QUICK-CHANGE ANALYTICAL CHAMBER

Modular for easy servicing, routine replacement of quartz sampling filter, or exchange of heating elements.

PHYSICAL SPECIFICATIONS

- Constructed in standard 19-inch rack-mount chassis.
- Dimensions (HxWxD): 42 x 48 x 60 cm (17" x 19" x 24")
Height required for inlet assembly: 120 cm (4 feet)
- Weight: 50 kg (110 lbs)
- Electrical supply: 100~240 VAC, 50/60 Hz
- Power consumption (maximum): 100 W sampling, 600 W analysis (typical 1-minute duration).
- Internal sampling pump: dual diaphragm, brushless speed-controlled DC motor, stabilized flow.
- Modular internal hardware for rapid servicing.
- Constructed in fully-enclosed, self-contained rack-mount chassis.

INSTALLATION REQUIREMENTS

Indoor or laboratory use, rack or benchtop.

Ambient environment 10°C ~ 35°C, non-condensing.

ACCESSORIES

PM2.5 inlet (PN 4117)

Shockproof and waterproof transit case (PN TCA08 4 02 001)

Air flow calibrator (BGI TetraCal) (PN7950)

Tube coupling fixed (PN TCA08 8 03 003)

Tube coupling (PN TCA08 8 03 004)

Sample line system (consists of tubes of different lengths, curvatures, 14/18mm diameter) (PN TCA08 8 22 000)

Filter Cartridge (for Clean Air performance test) (PN8072)

CONSUMABLE & OPERATIONAL SUPPLIES

47-mm. quartz fiber filters, package of 25 (PN TCA08 5 01 006)

Cartridge filter (PN 8072)

Capsule filter (PN TCA08 9 03 002)

EXCHANGE SERVICE COMPONENTS

VOC Denuder Cartridge (PN TCA08 5 01 004)

Analytical Chamber Assembly (PN TCA08 8 01 000)



Scan the code for more info

GENERAL INQUIRIES:

Aerosol d.o.o., Kamniška 39 A, SI-1000 Ljubljana, Slovenia
tel: +386 1 439 1700 fax: +386 59 191 221 www.aerosol.eu

US:

Sonoma Technology, 1450 N. McDowell Blvd., Suite 200, Petaluma, CA 94954

Email: MageeSales@SonomaTech.com

Phone +1 707-665-9900 Ext. 686 | Fax: +1 707-665-9800

www.sonomatech.com | www.mageescientific.com

or the distributor responsible for your country.